



SCANTEAM[®] 5750 Series Industrial Hand Held Laser Scanner

The SCANTEAM 5750 Hand Held Laser scanner is Hand Held Products' high performance industrial laser. It combines our best laser scanning performance with our most rugged design, and our traditionally excellent decoding, interfacing, and product durability reputation. The SCANTEAM 5750 is available in a decoded output configuration with PC compatible keyboard wedge, wand emulation, and TTL level RS-232 interfaces.

Hand Held Products laser scanners are comfortable to use, rugged, durable, and easy to program. They offer a wide selection of cables, upgradable Flash memory, and Quick*Load, a Windows[®] based programming tool, to maximize flexibility.

The SCANTEAM 5750 is a high performance scanner suitable for any general purpose application. It offers the widest range of resolution and reading distance of any Hand Held Products scanner. The SCANTEAM 5750 can be used in warehouse, factory and office automation, inventory, asset tracking, and transportation applications. It also offers Dual Interface. With a simple cable change, the scanner automatically switches interfaces (e.g., from keyboard wedge to portable data collection), increasing functionality and cost effectiveness.

Features & Benefits

Rugged Design

Durable products that survive in harsh industrial applications.

Sealed Housing

Meets IP-54 requirements.

Excellent Scanning Performance

Reads down to 5 mil codes. Working distance up to 31 inches (78.7 cm).

Auto Scanning

Hands free scanning option for faster throughput.

Dual Interfaces

A simple cable change automatically allows one scanner to be used on two terminal interfaces.

Flash Memory

Field upgradable memory extends the useful life of the product.

PC-Based Programming

*Product easily configured using Quick*Load programming utility.*

Performance

Scan Element:	Mylar resonant scan element		
Scan Rate:	36 scans per second		
	5750A	5750HD	5750ALR
Light Source:	650nm VLD	670nm VLD	650nm VLD
Laser Power:	.8 mW ± 10%	.36 mW ± 10%	1.5 mW ± 10%
Print Contrast:	25% MRD	40% MRD	40% MRD
Skew Angle:	± 65° min. from normal	± 60° min. from normal	± 60° min. from normal
Pitch Angle:	± 55° min. from normal	± 65° min. from normal	± 65° min. from normal

Working Range:

5750A:	5 mil	55 mil
Near	2 in. (5.1 cm)	ACAP
Far	4 in. (10.2 cm)	35 in. (88.9 cm)
5750HD:	3.0 mil	13 mil
Near	1.25 in. (3.2 cm)	1.75 in. (4.4cm)
Far	2.6 in. (6.6 cm)	6 in. (91.4 cm)
5750ALR:	13 mil	100 mil retroreflective
Near	20 in. (51 cm)	10.25 ft. (3.1m)
Far	37 in. (94 cm)	26.8 ft. (8.2m)

Mechanical/Electrical

Dimensions

Weight:	7 oz. (198g)
Length:	5.8 in. (14.8cm)
Width:	3 in. (7.5 cm)
Laser Classification:	CDRH Class II, ALR is Class III a in Europe


Power Requirements

Voltage:	Decoded Output: +5VDC	
Current Draw:	Idle	Scanning
All Models	95mA*	200mA max

*When operated in switched power mode, idle current is less than 0.06mA.

Environmental

Ambient Light:	Sunlight: 8000 ft. candles
Temperature Ranges	
Operating:	32°F to 122°F (-0°C to 50°C)
Storage:	-22°F to 158°F (-27°C to 63°C)
Humidity:	0% to 95% (non-condensing)
Shock:	26 drops from 6 ft. (1.8 m)
Agency Conformance:	Compiles with FCC Class B CE, UL, cUL listed, TÜV, EN55022 CISPR22 Class B
Environmental:	MIL-STD-810E, 506.3, #2, Drip MIL-STD-810E, 510.3, #1, Wind Blown Dust IP-54
Electrostatic Discharge:	15kv to any external surface
Symbologies:	UPC-EO, E1, A; EAN; JAN; ISBN all versions with supplement suppression; Codes 3 of 9; 128; I 2 of 5; 2 of 5; Matrix 2 of 5; 11; 93; MSI; Plessey; and Codabar



Worldwide Offices

Offices Serving North America

Skaneateles Falls, NY
Tel: (315) 685-8945
Fax: (315) 685-3172
Charlotte, NC
Tel: (704) 537-1444
Fax: (704) 532-4191

Offices Serving Europe, Middle East, and Africa

Europe
Tel: Int +31 (0) 40 24 24 486
Fax: Int +31 (0) 40 24 25 672
United Kingdom
Tel: Int +44 (0) 1 925 240055
Fax: Int +44 (0) 1 925 631280
France
Tel: Int +33 (0) 1 461 04111
Fax: Int +33 (0) 1 461 04120

Germany
Tel: Int +49 (0) 7 477 151377
Fax: Int +49 (0) 7 477 151378
Offices Serving Asia and the Pacific Rim
Hong Kong
Tel: Int +852 2511 3050/2511 3132
Fax: Int +852 2511 3557

Japan
Tel: Int +813 52127392
Fax: Int +813 32617372
Offices Serving Latin America
Naples, Florida
Tel: (941) 263-7600
Fax: (941) 263-9689